

DATA SHEET

Product overview

Fully enclosed, self-supporting structure

Neither pits nor separate drive unit required

Installation in just 1.5 days

Suitable for pallets, roll cages or hand trolleys

Modular system for installation on finished flooring

Mezzanine Goods Lift ML

Hydraulic goods lift in accordance with Machinery Directive 2006/42/EC for accessing unused storage space.



Product versions	External dimensions (W x L)	Internal dimensions (W x L)
Typ A	2700 × 2140 mm	2350 × 1500 mm
Typ B	2700 × 2340 mm	2350 × 1700 mm
Typ C	2700 × 2540 mm	2350 × 1900 mm
Typ D	2800 × 2140 mm	2450 × 1500 mm
Typ E	2800 × 2340 mm	2450 × 1700 mm
Typ F	2800 × 2540 mm	2450 × 1900 mm
Typ G	2900 × 2140 mm	2550 × 1500 mm
Typ H	2900 × 2340 mm	2550 × 1700 mm

Lifting capacity	up to 1.500 kg
Lifting height	up to 6.200 mm

Die vorstehenden Informationen, insbesondere Angaben und Darstellungen, sind unverbindlich und stellen keine Beschaffensvereinbarung und keine Garantie dar. Änderungen und Irrtümer ausdrücklich vorbehalten. Das Datenblatt ist urheberrechtlich geschützt. Nachdruck, auch auszugsweise, nur mit unserer Genehmigung.

Product description	• Standard / ○ Option
Lifting capacity	
1.000 kg	•
1.500 kg	○
Safety gate configuration	
Same side	•
Through car	•
Platform sides and gates	
1100 mm (h) platform sides and gates	•
1800 mm (h) platform sides and gates	○
Cladding	
Ply lined	•
Aluminium lined	○
Access Ramp	
2100 (W) x 1000 (L) x 75 mm (H)	•
2100 (W) x 500 (L) x 75mm (H)	○
Colour	
BS 10A05 Goosewing Grey	•
RAL 5002 Blue	○
RAL 2004 Orange	○
RAL 3000 Red	○
RAL 6005 Green	○
Operator Controls	
Positive pressure push button – Dead Man Controls 4 cycles per hour, over an 8-hour period	•
Auto dispatch and receive system - call/send lift at each landing Greater than 4 cycles per hour, over an 8-hour period	○
Power Requirements	
240V; 2.2kW; DOL; 16A type D motor rated circuit breaker	•
415V; 5.5kW; DOL; 16A type D motor rated circuit breaker - 3 Phase	○
Engine power	
Single phase: 1.8 kW	•
3 phase: 5.5 kW	○
Lifting speed	
80 mm / Sec.	•
Installation	
Optional - Installed into a pit	○
We will be happy to provide you with a quote for the installation on request.	