

## DATA SHEET

### Product line



**Removable with closed base**

### Additional functions with corresponding equipment



**Coating in RAL to choose**

## R 220-600

The removable bollard is especially suitable for very infrequent use (approx. 2 cycles/day).

- Can be detached without tools
- Ground-level fitting
- Locking via security lock with profile half cylinder
- No floor opening when bollard is removed



### Technical data

<b>Version</b>	Removable with closed base
<b>Diameter</b>	220 mm
<b>Material thickness</b>	4 mm
<b>Height</b>	600 mm
<b>Cylinder weight</b>	19 kg
<b>Load class according to EN 124</b>	C250
<b>Cycles (approx. per day)</b>	2
<b>Impact energy with destruction</b>	150000 J
<b>Impact energy without destruction</b>	40000 J

Equipment		Function
Cylinder cover	Aluminium with protection against corrosion	●
Cylinder surface	Steel S235JR – stainless steel V2A (AISI 304)	●
Surface treatment	Steel version: steel coated (Anthracite grey) Stainless steel version: stainless steel coated (Anthracite grey) or brushed	●
Reflecting strips	Improved visibility at night, all-round	●
Floor fitting	Ground fitting with cylinder bearing made of steel, painted, with round bottom plate	○
Profile half cylinder lock	Improved security against removal by unauthorized personnel	●

● Standard ○ Optional



The information above, in particular the specifications and illustrations, is not binding and does not constitute an agreement on quality or a guarantee. Changes and errors are expressly reserved. The data sheet is subject to copyright. No part may be reproduced without our prior permission.